



## Technical Data Sheet

Updated: 06/08/2022

### **HOT SHOT'S SECRET® LX4 Lubricity Extreme Fuel Pump & Injector Lubricator**

#### **Product Overview**

LX4 Lubricity Extreme is a premium lubricity additive and fuel conditioner for Ultra Low Sulfur Diesel (ULSD) and gasoline. LX4 Lubricity Extreme contains the highest level of lubricity performance on the market and can put even the poorest quality fuel back into specification to meet engine manufacturer's requirements for lubrication.

It was developed to greatly increase fuel system lubrication and prevent the wear and scarring of key components inside the fuel system, including pumps and injectors. Protect your vehicles fuel system with the highest level of protection available from LX4 Lubricity Extreme and improve fuel economy, efficiency and reliability.

**Applications and Uses** LX4 Lubricity Extreme is recommended for use in all diesel and gasoline engines.

#### **Benefits**

- Protects fuel pumps and injectors from wear and failure
- Lubricates upper cylinder
- Increases diesel fuel's lubricity
- Specially formulated for Ultra Low Sulfur Diesel (ULSD)
- 2x more lubricity than the leading competitor
- Zero alcohol or harmful solvents
- Improves fuel economy
- Reduces pintle scoring and wear
- Will not void manufacturer's warranty
- Safe for particulate filters
- Reduces fuel system wear

When Ultra Low Sulfur Diesel was mandated for on-road diesels in 2007, the lubrication of diesel fuel was diminished. LX4 Lubricity Extreme improves diesel fuel's lubrication, putting even the poorest quality fuel back into specification, protecting fuel systems from wear and failure.



### Directions for Use

Use LX4 Lubricity Extreme with every fill-up.

Fuel	Hot Shot's Secret LX4 Lubricity Extreme
20 gallons	2 ounces
80 gallons	8 ounces
400 gallons	40 ounces

### Packaging

LX4 Lubricity Extreme is available in:

- 16-ounce round bottle (1/2 quart)
- 16-ounce squeeze bottle (1/2 quart)
- 32-ounces (1 quart)
- 64-ounces (2 quart)
- 128-ounces (1 gallon)

### Typical Properties

Property or Test	Result
API gravity	25.59
Flash point, °F	363.2
Pour point, °F	32
Ash content	0
Color	Gold